# Introducing GENII



# THE ULTIMATE FASTENERS

316 STAINLESS STEEL

STRUCTURAL LAG



NEW! 316 STAINLESS STEEL



#### Horizon Curve™

A slight curvature of the head for elegant, professional, architectural results. Whether countersinking or surface mounting, the results are impressive!



## **Locking Wedges**

The locking wedges help to mill and countersink the head into the wood for a clean finish. It also locks the head into place preventing unwanted future movement.



#### Twin Blades™

Patented<sup>(2)</sup> Twin Blades knurls cut fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.



#### **Fast Start Tip**

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

The advanced Heavy Duty Structural Lag Screw in **316 Stainless Steel** for typical high corrosive, environments. Great for any size job or project.



Available in 50ct packaging.

### WWW.SCREW-PRODUCTS.COM

Gig Harbor, WA • Bradenton, FL Toll-Free 1-877-844-8880

THE ULTIMATE FASTENERS





The NOVA™ Structural Lag is the superior lag screw for any of your projects. With a strong thread that ensures maximum withdrawal strength and extra sharp Fast Start Tip that easily grips and cuts its way through the wood, you will feel the power and quality of the NOVA. The Self-Tapping Thread cuts effectively through materials such as wood, plastic and sheet metal. The patented<sup>(2)</sup> Twin Blades™ ensure minimum friction on the shank and the Locking Wedges under the head countersink perfectly with maximum wood contact.







#### TOUGH ENVIRONMENTS

**Stainless Steel AISI 316** is code compliant for use in marine environments with saltwater splash, airborne salts, and areas with de-icing salts.

# **Common Applications**

- Commercial & residential
- Timber
- Ledgers, posts & beams
- Rigid Foam Insulation
- Roofing
- · Deck framing
- Docks
- And much more!

#### Sizes Available: #16 x 2-1/2" to #16 x 6"

General Info	
Type of Screw	General Purpose Wood
Material	316 Stainless Steel
Head Style	Low Profile TX30 Star Drive
Point Type	Modified Type 17

Construction	#16
Head Diameter (Inch)	0.630"
Minor Thread Diameter	0.177"
Major Thread Diameter	0.283"
Shaft Diameter	0.205"
Drive Size	TX30
Product Range	Thread Length
Length	#16
2-1/2"	1-1/2"

Product Range	Thread Length
Length	#16
2-1/2"	1-1/2"
3"	1-1/2"
4"	2"
5"	3"
6"	3"



