Introducing GENIII



THE ULTIMATE FASTENERS

#18x 5/16" HEX HEAD

STRUCTURAL LAG

YUKON

DrJ TER 2010-03
Technical Evaluation
Report
available now at

available now at www.screw-products.com



Large Washer Hex Head

Strong Structural Lag screw with 5/16" Hex Head for a powerful torque transmission and easy installation. The built-in washer underneath the head provides great holding power and works well for heavy duty applications.

Twin Blades™

Patented⁽²⁾ Twin Blades knurls cut fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.

Fast Start Tip

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

The advanced Heavy Duty Structural Lag Screw with **ZYTEC™GX** corrosion protection coating for exterior environments. Great for any size job or project.



Available in 50ct and 250ct.
All Packaging Includes Hex Driver.

WWW.SCREW-PRODUCTS.COM

Gig Harbor, WA • Bradenton, FL Toll-Free 1-877-844-8880

THE ULTIMATE FASTENERS

(1) Patent # 11,346,388 B2 (2) Patent # 11,359,661 B2













TYPICAL EXTERIOR USE

ZYTEC™GX Coating: Tested and recognized for use in most ground contact pressure treated lumber for general exterior construction as described by the American Wood Protection Association (AWPA) U1 UC4A or below. Always follow timber manufacturer's recommendations for fasteners.

Common Applications

- Commercial & residential
- **Landscaping Timbers**
- Heavy duty lumber
- LVL (Laminated Veneer Lumber)
- Deck framing
- Ledgers
- Posts
- **Beams**
- And Much more!

TER 2010-03 Technical Evaluation Report

available now at www.screw-products.com

Sizes Available: #18 x 4" to #18 x 11"

General Info		
Type of Screw	Hex Head Structural Wood Screw	
Material	Heat Treated, Hardened Steel	
Coating	ZYTEC™ GX	
Head Style	5/16" F	Hex Head
Point Type	Modified Type 17	
Construction		#18
Head diameter (inch)		0.630"
Minor thread diameter		0.205"

Minor thread diameter	0.205"
Major thread diameter	0.315"
Shaft diameter	0.226"
Drive Size	5/16" HEX
Product Range	#18
Length	Thread
4"	2"
5"	2-3/4"

2-3/4"

2-3/4"

2-3/4"

2-3/4"









THE ULTIMATE FASTENERS

6"

7"

9"

11"